



LEAD-ACID RANGE GAMME PLOMB-ACIDE

GEL

**GEL high performance
GEL haute performance**



NON-SPILLABLE



The GEL battery range is designed to offer maximum performance and safety! Ready to use, the GEL battery will not require any acid handling, initial preparation or maintenance. Its non spillable design (VRLA) linked to its high performance will make it the ideal battery for all powersports.

La gamme de batteries GEL est conçue pour offrir un maximum de performances et de sécurité ! Prête à l'emploi, la batterie GEL ne demandera aucune manipulation d'acide, de préparation initiale ni d'entretien. Sa conception 100% étanche (VRLA) liée à ses hautes performances en feront la batterie idéale pour tous les sports mécaniques.

FEATURES / CARACTÉRISTIQUES

- GEL technology ▪ Technologie GEL
- Ready to use ▪ Prête à l'emploi
- Factory activated ▪ Activée en usine
- VRLA battery ▪ Batterie VRLA
- Non spillable: easy to ship ▪ Étanche : facile à expédier
- 100% maintenance free ▪ 100% sans entretien
- Multi-positional fitment ▪ Montage dans toutes les positions
- Minimized plate sulfation ▪ Sulfatation interne minimisée
- Suitable for cold weather ▪ Adaptée par temps froid
- No acid handling ▪ Aucune manipulation d'acide
- Easy to install ▪ Facile à installer
- Increased life time ▪ Durée de vie plus longue

COMPATIBLE CHARGERS / CHARGEURS COMPATIBLES

**FULLLOAD F4 FULLLOAD 1000
FULLLOAD 1500 FULLLOAD 750**

Fulbat designation	Voltage V	Capacity Ah (10h)	Capacity Ah (20h)	CCA A (-18°C/0°F)	Dimensions mm (±2mm)			Assembly drawing	Terminal drawings			
					L	W	H		Front	Side	Top	3D
FB4L-B	12	5	5.3	50	120	70	92					
FB9-B (12N9-4B-1)	12	9	9.5	115	135	75	139					
FB12AL-A2	12	12	12.6	150	134	80	161					
FB14L-A2 (12N14-3A)	12	14	14.7	175	135	90	167					
FB14-A2 (12N14-4A)	12	14	14.7	175	135	90	167					
FTX5L-BS	12	4	4.2	80	113	70	105					
FTX7L-BS	12	6	6.3	100	113	70	130					
FTX7A-BS	12	6	6.3	90	150	87	93					
FTX9-BS	12	8	8.4	135	150	87	105					
FT12A-BS	12	10	10.5	175	150	88	105					
FTX12-BS	12	10	10.5	180	150	87	130					
FTX14-BS	12	12	12.6	200	150	87	145					
FTX16	12	14	14.7	230	150	87	161					
FTX20HL-BS	12	18	18.9	310	175	87	155					
FTX4L-BS / FTZ5S	12	4	4.2	70	113	70	85					
FTZ7S	12	6	6.3	130	113	70	105					
FTZ8V	12	7	7.4	120	113	70	130					
FT7B-4	12	6.5	6.8	110	150	65	93					
FT9B-4	12	8	8.4	120	150	68	105					
FTZ10S	12	8.6	9.1	190	150	88	93					
FTZ12S	12	11	11.6	210	150	88	110					
FT12B-4	12	10	10.5	210	150	69	130					
FTZ14S	12	11.2	11.8	230	150	88	110					
FT14B-4	12	12	12.6	210	150	69	145					
F50-N18L-A (12N18-3A)	12	21	22.1	350	205	87	162					
53030 (F60-N30L-A)	12	30	31.6	300	186	130	171					

BMW & HARLEY DAVIDSON

High capacity reinforced battery / Batterie haute capacité et renforcée

Fulbat designation	Voltage V	Capacity Ah (10h)	Capacity Ah (20h)	CCA A (-18°C/0°F)	Dimensions mm (±2mm)			Assembly drawing	Terminal drawings			
					L	W	H		Front	Side	Top	3D
NH12-20	12	20	21.1	235	182	77	168					
FHD14HL-BS	12	14	14.7	220	150	87	145					
FHD20HL-BS	12	20	21.1	310	175	87	155					
FHD30HL-BS	12	30	31.6	430	165	125	175					

