


LITHIUM (LiFePO4) RANGE

GAMME LITHIUM (LiFePO4)

LITHIUM
LiFePO4

LITHIUM

High performance & lightweight
Haute performance & légère



COMPATIBLE CHARGERS / CHARGEURS COMPATIBLES

FULLOAD 1000
FULLOAD 750

The new Lithium range is designed to offer the ultimate riding experience. With ultra-light weight conception, this LiFePO4 range will ensure faster acceleration, higher performance, very low self-discharge and extreme cycle life. Fulbat Lithium range is ideal for the most demanding riders.

La nouvelle gamme Lithium est conçue pour offrir une expérience de conduite unique. De conception ultra légère, la gamme LiFePO4 garantira une accélération plus rapide, des performances plus élevées et une durée de vie extrême. Cette gamme Lithium est idéale pour les motards les plus exigeants.

FEATURES / CARACTÉRISTIQUES

- Ultra lightweight ▪ Poids ultra léger
- Outstanding safety features ▪ Sécurisée et sûre
- Maintenance free and ready to use ▪ Sans entretien et prête à l'emploi
- Fast charging capabilities ▪ Charge rapide de la batterie
- High cold cranking performance ▪ Haute performance de démarrage à froid
- Long life time ▪ Longue durée de vie
- Very low self-discharge ▪ Très faible autodécharge
- Environmental friendly ▪ Respectueuse de l'environnement
- Integrated battery tester ▪ Testeur de batterie intégré

| Fulbat designation 12V | Energy Wh | Capacity (10Hr) Ah | CCA (A) | Dimensions (±2mm) | | | Layout | Charging current (A) | | Equivalent Lead Acid battery types (most popular models) |
|------------------------|-----------|--------------------|---------|-------------------|----|-----|--------|----------------------|-----|--|
| | | | | L | W | H | | Std | Max | |
| FLTK01 | 24 | 2 | 140 | 86 | 48 | 90 | - + | 1 | 4 | KTM OE replacement |
| FLT75S | 20.5 | 1.6 | 110 | 113 | 70 | 85 | - + | 0.8 | 3.2 | FTX4L-BS/FTZ5S-BS;FTX5L-BS |
| FLTZ7S | 25.6 | 2 | 140 | 113 | 70 | 85 | - + | 1 | 4 | FTZ7S;FTZ8V |
| FLTX7L | 30.7 | 2.4 | 170 | 113 | 70 | 85 | - + | 1.2 | 4.8 | FTX7L-BS |
| FLT9B | 38.4 | 3 | 210 | 150 | 66 | 93 | + - | 1.5 | 6 | FT7B-4;FT9B-4;FT7B-BS;FT9B-BS |
| FLTX9 | 38.4 | 3 | 210 | 150 | 87 | 105 | + - | 1.5 | 6 | FTX9-BS |
| FLTZ10S | 51.2 | 4 | 280 | 150 | 87 | 93 | + - | 2 | 8 | FTZ10S |
| FLT12B | 64 | 5 | 350 | 150 | 66 | 130 | + - | 2.5 | 10 | FT12B-4;FT14B-4;FT12B-BS;FT14B-BS |
| FLTX12 | 44.8 | 3.5 | 250 | 150 | 87 | 93 | + - | 1.8 | 7 | FTX7A-BS;FTX12-BS;FT12A-BS |
| FLTX14H | 51.2 | 4 | 280 | 150 | 87 | 93 | + - | 2 | 8 | FTX14-BS |
| FLTZ14S | 64 | 5 | 350 | 150 | 87 | 93 | + - | 2.5 | 10 | FTZ12S;FTZ14S |
| FLTX20H | 89.6 | 7 | 420 | 175 | 87 | 130 | + - | 3.5 | 14 | FTX20-BS |
| FLTX20HL | 89.6 | 7 | 420 | 175 | 87 | 130 | - + | 3.5 | 14 | FTX20L-BS;FTX20HL-BS;FHD20HL-BS |