

SLA RANGE

Ready to use & non-spillable

SLA battery range is designed to offer maximum performance and safety! Ready to use, the Sealed Lead Acid (SLA) battery will not require any acid handling, initial the preparation or maintenance. Its non-spillable design (VRLA) linked to its high performance make it the ideal battery for all ride-on mowers.

FEATURES


- ✔ AGM technology
- ✔ Ready to use
- ✔ Easy to install & maintenance free
- ✔ Factory activated (VRLA)
- ✔ Non-spillable: easy to ship
- ✔ No acid handling
- ✔ Higher life cycle
- ✔ Minimized plate sulfation
- ✔ Suitable for cold weather



COMPATIBLE CHARGERS

- ✔ Fulload 1000
- ✔ Fulbank 2000
- ✔ Fulload F4

NON-SPILLABLE



Fulbat designation	Voltage (V)	Capacity Ah (10h)	Capacity Ah (20h)	CCA A (-18°C)	Dimensions (±2mm)			Assembly drawing	Terminal 3D
					L	W	H		
U1-9 SLA (12N24-4A)	12	-	28	300	195	125	176		
U1R-9 SLA (12N24-3A)	12	-	28	300	195	125	176		
U1-12 SLA (12N24-4A)	12	-	32	400	195	125	176		
U1R-12 SLA (12N24-3A)	12	-	32	400	195	125	176		
SLA12-18	12	18	18.9	150	182	77	168		
SLA12-20	12	20	21.1	180	182	77	168		
SLA12-22	12	22	23.1	210	182	77	168		
FTX16	12	14	14.7	230	150	87	161		
FTZ7S	12	6	6.3	130	113	70	105		
FB14L-A2 (12N14-3A)	12	14	14.7	175	135	90	167		
FB14-A2 (12N14-4A)	12	14	14.7	175	135	90	167		
F50-N18L-A (12N18-3A)	12	21	22.1	350	205	87	162		
53030 (F60-N30L-A)	12	30	31.6	300	178	123	166		
FBS1225	12	2.5	2.6	25	112	88	69		
FBS1225L	12	3	3.2	25	223	44	69		