# **FL-RM03** Datasheet







FL Series is a complete range of batteries for robot mowers specially designed for intensive charge and discharge use.

Equipped with high-quality and high-capacity lithium cells, this range thus offers the robot great autonomy in working.

Ar SPECIFICATIONS	
Nominal voltage	25.6V (26650 - 8S2P)
Nominal capacity	6Ah
Energy	153.6Wh
Technology	LiFePO4
Brand cells	-
Protection function (PCM)	Over charge protection/ Over discharge protec- tion/Over current protec- tion/Temperature protec- tion/Balanced function
<b>Standard charge</b> Max charge current	6A (29.2V max)
<b>Standard discharge</b> Standard discharge current Max discharge current	1.2A (cut-off voltage: 16V) 30A
<b>Operating temp. range</b> Charge temperature Discharge temperature Storage temperature	0°C to 45°C -10°C to 60°C 0°C to 40°C

## 

Length	212.7±2mm
Width	53±2mm
Total Height	74.9±2mm
Gross weight	1.47 kg

### A TERMINAL



#### **APPLICATIONS**



#### **₩ FEATURES**

- Compatible battery type
- High cycle life
- Long battery life: capacity sometimes higher than the original battery
- High quality lithium cells
- More than 200 models of robots covered

## COMPATIBILITY (LIST NOT EXHAUSTIVE)

- ROBOMOW RS612, RS622, RS635, RS1000, RS1800, RS3000
   WOLF GARTEN
- RS1000, RS1800, RS3000
- CUB CADET
  3000