

# SLA RANGE

Ready to use & non-spillable

SLA battery range is designed to offer maximum performance and safety! Ready to use, the Sealed Lead Acid (SLA) battery will not require any acid handling, initial preparation or maintenance. Its non-spillable design linked to its high performance make it the ideal battery for all ride-on mowers.

## FEATURES


- AGM technology (factory activated)
- Ready to use
- 100% maintenance free
- Non-spillable: easy to ship
- Higher cycle life
- Ultra safe & highly vibration resistant
- Minimized plate sulfation
- Suitable for cold weather



## COMPATIBLE CHARGERS

- Fulload 1000
- Fulbank 2000
- Fulload F4

**NON-SPILLABLE**



Fulbat designation	Voltage (V)	Capacity Ah (10h)	Capacity Ah (20h)	CCA A (-18°C)	Dimensions (±2mm)			Assembly drawing	Terminal 3D
					L	W	H		
<b>U1-9 SLA (12N24-4A)</b>	12	-	28	300	195	125	176		
<b>U1R-9 SLA (12N24-3A)</b>	12	-	28	300	195	125	176		
<b>U1-12 SLA (12N24-4A)</b>	12	-	32	400	195	125	176		
<b>U1R-12 SLA (12N24-3A)</b>	12	-	32	400	195	125	176		
<b>SLA12-18</b>	12	18	18.9	150	182	77	168		
<b>SLA12-20</b>	12	20	21.1	180	182	77	168		
<b>SLA12-22</b>	12	22	23.1	210	182	77	168		
<b>FTX16</b>	12	14	14.7	230	150	87	161		
<b>FTZ75</b>	12	6	6.3	130	113	70	105		
<b>FB14L-A2 ( 12N14-3A)</b>	12	14	14.7	175	135	90	167		
<b>FB14-A2 ( 12N14-4A)</b>	12	14	14.7	175	135	90	167		
<b>F50-N18L-A (12N18-3A)</b>	12	21	22.1	350	205	87	162		
<b>53030 (F60-N30L-A)</b>	12	30	31.6	300	178	123	166		
<b>53034 (F60-N30-A)</b>	12	30	31.6	300	178	123	166		