FDC12-75

Datasheet









FDC Series are Deep Cycle AGM Carbon batteries specifically designed for frequent discharge deep cycle application. With non-spillable design and maintenance free, AGM FDC Series offer low self-discharge and ensure a maximum service life with high resistance to cycles. Thanks to carbon additives, these batteries can perfectly be used with good performance without being 100% charged. This range offers reliable performance for electric vehicle and other applications such as golf cart, aerial work platform, cleaning machine, marine, solar energy...

₼ **FEATURES**

- Deep Cycle AGM technology (VRLA)
- Non-spillable & maintenance free
- No acid handling
- Deep Cycle design for high capacity and maximum life
- Reinforced grid/plates design for optimal cyclic use
- Robust, safe & reliable
- Carbon additives to perform in Partial State of Charge (PSOC) and to increase charging efficiency
- Low self-discharge rate for longer shelf life

Voltage

Capacity

Reserve capacity

12 V

82 Ah (20hr) **160 min** (25A)

75 Ah (10hr)

71 Ah (5hr)

65 Ah (3hr)

53 min (56A)

OPERATING TEMPERATURE


Discharge	-15°C ~ 50°C
Charge	0°C ~ 40°C
Storage	-15°C ~ 40°C


CHARGING INSTRUCTIONS


Max current	17.0A
Float	13.6V - 13.8V
Cyclic	14.7V - 14.8V

→ DIMENSIONS & WEIGHT

Length	260±2mm
Width	168±2mm
Total Height	214±2mm
Gross weight	23.3kg








A TERMINAL





APPLICATIONS



Aerial work platform





Floor cleaning machine














FDC12-75

Datasheet









SELF-DISCHARGE CHARACTERISTIC

