

FL-AL02

Datasheet



FL SERIES is a complete range of batteries for robot mowers specially designed for intensive charge and discharge use.

Equipped with high-quality and high-capacity Lithium cells, this range thus offers the robot great autonomy in working.

FEATURES

- » Compatible battery type
- » High cycle life
- » Long battery life: capacity sometimes higher than the original battery
- » High quality Lithium cells
- » More than 200 models of robot covered

COMPATIBILITY (LIST NOT EXHAUSTIVE)

- **AL-KO**
Robolinho 3000, 4000, 82.8, 116


SPECIFICATIONS

Nominal voltage	25.2V (18650 - 7S2P)
Nominal capacity	5Ah
Energy	126Wh
Technology	Lithium-ion
Brand cells	-
Protection function (PCM)	Over charge protection/ Over discharge protection/ Over current protection/ Temperature protection/ Balanced function
Standard charge	
Max charge current	2.5A (21V max)
Standard discharge	
Standard discharge current	1A (cut-off voltage: 12.5V)
Max discharge current	15A
Operating temp. range	
Charge temperature	0°C to 45°C
Discharge temperature	-10°C to 60°C
Storage temperature	0°C to 40°C

DIMENSIONS & WEIGHT

Length	128±2mm
Width	69±2mm
Total Height	50±2mm
Gross weight	0.69kg

TERMINAL



APPLICATIONS



Lawn & garden